



1、 Description

Fiber optic pigtails provide a fast way to make communication devices in the field. They are designed, manufactured and tested according to protocol and performance dictated by the industrial standards, which will meet your most stringent mechanical and performance specifications.

2、 Features

- 100% factory tested assemblies with traceable test data, Low environmental sensitivity
- Low insertion loss, High return loss, Stricter than industry standards
- Good exchange ability and good durability, Stable optical properties
- Standard connector, Various connector option: LC、 SC、 FC、 ST、 E2000、 MU、 DIN etc.
- Compliant with IEC61754, GR-326, TIA/EIA 568 standard

3、 Specification

Fiber Type	SM (9/125um)		MM (50/125um、 62.5/125um)
Polish	UPC	APC	UPC
Insertion Loss (typical)	≤0.30dB		≤0.30dB
Return Loss	≥50dB	≥60dB	≥20dB
3D	Radius of Curvature :10-25mm(PC/UPC) , 5-12mm(APC) Apex offset : 0-50um High fiber : ±100 nm Angle: 8±0.2°(APC)		

Repeatability	1000 times typical change value $\leq 0.20\text{dB}$
Interchangeability	$\leq 0.20\text{dB}$
Cable Diameter	0.9mm
Jacket Material(optional)	LSZH、OFNP、OFNR、PVC
Fiber Moder(optional)	G652D, G657A, G657B, OM1, OM2, OM3, OM4
Operating Temperature	-20 ~ +70 °C
Storage Temperature	-40 ~ +85 °C

TBF color code sequence

	1	2	3	4	5	6
TBF Color	Blue	Orange	Green	Brown	Slate	White
	7	8	9	10	11	12
	Red	Black	Yellow	Purple	Pink	Aqua

4、Application

- CATV, LANs, WANs
- Telecommunication networks
- Active device termination
- Data center system networks
- Video and military active device termination